

## Setup Sheet for Team Associated's RC8

**Reset Fields Rev. 3**

### :: Front Suspension

anti-roll bar:

- 2.2 - black
- 2.5 - silver
- 2.8 - gold

steering rack:

- back
- mid
- front

hinge pin  
bushing

# 2F / 1R

- up  down

camber: -2

caster: 16

toe: 0

kickup bushing

# 2

- up  down

ride height: 27 mm

### :: Rear Suspension

anti-roll bar:

- 2.2 - black
- 2.5 - silver
- 2.8 - gold

wheelbase:

- long
- medium
- short

camber: -2

toe: 3

hub:  
upper  
lower

anti-squat  
bushing

# 2

- up  down

ride height: 27 mm

### :: Front Shocks

spring: OFNA Blue piston: 1.3 x 6  
 shock fluid: 25 wt length: 2 mm Internal Limiting  
 shock cap: 16mm

### :: Rear Shocks

spring: OFNA White piston: 1.3 x 6  
 shock fluid: 30 wt length: 4mm Internal Limiting  
 shock cap: 16mm

### :: Differentials

front fluid: 10,000  
 center fluid: 20,000  
 rear fluid: 10,000

### :: Wing

location:  forward  back  
 angle:  low  med.  high  
 type: JConcepts

### :: Chassis Braces

standard  molded  aluminum  
 other: \_\_\_\_\_

### :: Engine

engine: Reedy restrictor: 7.5 mm  
 muffler: Factory Team 2035 temp: 230  
 glow plug: O.S. P3  
 fuel: TQ Fuel 30%

### :: Gearing/Clutch

gearing: 16/46  
 shoes: 3 x aluminum \_\_\_\_\_ x fiber  
 spring: \_\_\_\_\_ x .9mm 3 x 1.0mm \_\_\_\_\_ x 1.1mm  
 notes: 7075 Hard Clutch Shoes

### :: Notes

No steering rack, bolt directly to bellcranks & spindle; Receiver pack mounted next to servo on side guard

### :: Tires

tire (F/R): Proline Holeshots / Proline Holeshots  
 compound (F/R): XTR / XTR  
 insert: Proline Stock wheel: Associated 83mm

### :: Race and Vehicle Comments

qualify: 3rd main: A finish: 15th tq:   
 comments: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### :: Track Info

traction:  high  med.  low  
 surface:  smooth  bumpy  
 blue groove  soft dirt  grass  
 clay  wet  dusty  
 other: Surface resembled asphalt